

CARECLEAN CARBON

Liquid cleaning agent for use in immersion baths for removing partially carbonized oils

- Consists of yellow top layer and brown under layer.
- Top layer contains water and a corrosion inhibitor. This prevents evaporation of the volatile components in the under layer.
- Under layer is based on aromatic and chlorinated hydrocarbons, cresols and anionic surface active substances, which remove heavy oils and most carbon contamination.
- Not corrosive on common metals.

Application:

Careclean Carbon is applied undiluted for cleaning of highly soiled components. (e.g. cylinder heads, gear boxes, pistons, oil pumps, injectors, pipes, burners, tubes, coolers, oil filters.) Also old paint and lacquers can be removed with Careclean Carbon.

Directions for use:

Immersion baths

Put the components in a steel bath filled with undiluted Careclean Carbon and let them soak for 2 to 10 hours, depending on the degree of contamination. Then take out the components and flush clean with a powerful water-jet.

Properties

Careclean Carbon is a dual component liquid with a strong aromatic smell. It has no flash point, but when used in immersion baths the flash point may fall in time to 80°C. Plastics and rubber should first be tested for chemical attack.

Specific gravity : 1.1
Flash point PM CC : None
pH : Top Layer 11.7
Bottom Layer : 7.5

For detailed information on safety and health, please refer to Material Safety Data Sheet and / or Product label.

The details of our products are given completely free of undertaking. Since their application lies outside our control we cannot accept any liability for the results.