

CARECLEAN FILTER

Liquid cleaning agent for removal of partially carbonized oils using circulation method

- Based on a mixture of aliphatic and chlorinated aromatic hydrocarbons, cresols and anionic surface-active agents.
- Removes partially carbonized oils.
- Timely cleaning prevents the formation of coke-like adherents.
- Non-corrosive.

Application

Careclean Filter is mainly used for the cleaning of permanently fixed oil coolers, oil pre-heaters and metal/ceramic oil filters. These units are regularly contaminated by particles in the oil and partially carbonized oils. Timely cleaning prevents the formation of coke-like adherents which are difficult or impossible to remove.

Directions for use

Careclean Filter is used undiluted at cleaning temperatures not exceeding 60° C. The cleaning effect is obtained by filling and/or circulating the product. Cleaning will take 8 to 24 hours depending upon the degree of contamination.

Properties

Careclean Filter is a light brown colored fluid. Its formula includes cresols and chlorinated aromatic hydrocarbons. Plastics and rubber should first be tested for chemical attack. The product may also attack paints and lacquers.

Specific gravity : 1.04
Flashpoint PM CC : 62° C
pH (1% solution) : 8.7

For detailed information on safety and health, please refer to Material Safety Data Sheet and / or Product label.

The details of our products are given completely free of undertaking. Since their application lies outside our control we cannot accept any liability for the results.