

CARECLEAN RUST

Acidic liquid product for the cleaning of aluminium, copper and removal of rust stains on paint work.

- * Cleans and brightens aluminium and copper.
- * Removes rust stains without risk to paintwork.
- * Safe on most common metals.

Application

Careclean Rust is used for the cleaning of aluminium floor plates, copper and brass fittings, wooden decks and the removal of lime after tank cleaning operations.

Directions for use

In most cases Careclean Rust is applied by brush diluted in solutions ranging from 10-50% and left to react for 5-10 minutes. Smaller objects can be soaked in plastic container. After cleaning, rinse items thoroughly with a water jet.

Paintwork

Dilute Careclean Rust 1 liter of product to 4-9 liters water, apply the solution by brush or spray using plastic equipment and leave to soak for 10-20 minutes. Rinse off using a powerful water jet with a brush, if necessary.

Tankcleaning

If lime scale stains are present after completion of tank cleaning operations, inject 0.5 liters Careclean Rust per 100 liters washing water directly into the automatic washing system approx. 20 minutes. The recommended temperature is 75-85°C.

For detailed instructions on tankcleaning refer to the Marine Care Tank Cleaning Manual.

A range of support equipment is also available.

Properties

Colourless fluid contains phosphoric acid. Non-flammable and completely soluble in water. Within the reaction time suitable for use on all metals and painted surfaces.

Specific gravity (20°C)	: 1.21
Flash point CC	: none
pH (1% solution)	: 2.0

For detailed information on safety and health, please refer to Material Safety Data Sheet and / or Product label.

The details of our products are given completely free of undertaking. Since their application lies outside our control we cannot accept any liability for the results.