

CARECLEAN NEUTRAL HCF

Universal neutral liquid degreaser for the removal of vegetable oils and animal oils and fats from zinc-silicate coated tanks.

- * Neutral cleaning product based on highly efficient dissolving and low foaming nonionic surface active agents.
- * Especially developed for the removal of vegetable, animal and mineral oils as well as fats where cleaning with Careclean Alkaline Extra or Careclean Alkaline is not possible.
- * Suitable for cleaning tanks coated with zinc-silicate and all common metals.

Application

1. Careclean Neutral HCF can be used for the removal of vegetable and/or animal oils and fats and light mineral oils in aluminium and/or zinc-silicate coated tanks.
2. Careclean Neutral HCF can be used as an after treatment agent in hydrocarbon free cleaning operations where cleaning has been carried out with e.g. Careclean Degreaser HD or Careclean Degreaser GP.

Directions for use

Cleaning of tanks

Prewash before cleaning with Careclean Neutral HCF it is recommended to prewash with hot water at 50°C. For drying and semi-drying oils a prewash with cold water should be carried out immediately after discharge of cargo to retard oxidation and hardening of oil residues.

Recirculation method

A chemical solution is prepared in an empty slop tank or one of the after tanks near the pump room, circulated via the automatic tank washing system pump and heater to the tank to be cleaned, wherefrom the solution is returned to the chemical solution tank via the stripping line. Usually it is not possible to recirculate the chemical solution through the tank washing system heater (to maintain solution temperature) without making a temporary connection between the chemical solution tank and the tank washing pump. Capacities of solution tank, pipeline and pumps etc. should be calculated carefully to ensure sufficient volumetric quantity for a continuous recirculation.

Depending on size and condition of tanks to be cleaned and quantity of chemical solution, a drawback in this method is that usually only 3 (three) tanks can be cleaned with one solution after which a fresh solution should be made and heated before cleaning can continue.

Depending on the degree of contamination Careclean Neutral HCF is circulated as a 2-3% solution for a period of 2-6 hours. The water temperature should be approx. 20-60 °C. After the circulation period rinse thoroughly with water.

Spray method

Spray the hot tanksurfaces with undiluted Careclean Neutral HCF until the surfaces are well soaked and let the product act for at least 30 min. Then rinse all tank surfaces with water at max. 60°C for 45 minutes.

Hydrocarbonfree cleaning

Hand spray Careclean Neutral HCF on the hot tanksurfaces and let it act for 30 minutes. Rinse thoroughly with hot chloride free water when cleaning is completed. If fresh water is used, steam tanks afterwards to remove any chlorides which may cause delay in passing the chloride test for methanol etc.

For detailed instructions on tank cleaning refer to the Marine Care Tank Cleaning Manual. A range of support equipment is also available.

Properties

Neutral colourless liquid with a characteristic odour. Completely miscible with sea water and fresh water. Suitable for use on zinc-silicate coatings and most common metals. Limited application on epoxy coatings (maximum concentration 10% and maximum temperature 60°C)

Specific gravity (20%)	: 1.00
Flash point PM CC	: 74 °C
pH (1% solution)	: 7.00

For detailed information on safety and health, please refer to Material Safety Data Sheet and / or Product label.

The details of our products are given completely free of undertaking. Since their application lies outside our control we cannot accept any liability for the results.