

CARECLEAN ALKALINE EXTRA

Strong alkaline liquid degreasing agent for the removal of vegetable, fish and animal oils and fats from epoxy / polyurethane coated or stainless steel tanks by injection or circulation method.

- * Very powerful alkaline cleaning agent based on strong anionic surface active agents and alkaline salts.
- * Thorough saponification and emulsification provides economic removal of vegetable and animal oils.
- * Can be used on most common metals except aluminium, tin, zinc and galvanised metals.
- * Safe to use on epoxy and polyurethane coatings but it is not suitable for use on zinc silicate coatings, most paints and lacquers (For zinc silicate coating we advise the use of Careclean Neutral HCF).
- * Deodorises certain residues.

Application

Steam boilers

Prior to acid cleaning of steam boilers which are also contaminated with oil and grease or when silicates/calcium sulfates are present it is advantageous to first perform a boil out operation with Careclean Alkaline Extra.

Tanks

Suitable for the removal of fatty acids, fish oils and other drying or semi drying oil deposits present as deposits in storage and loading tanks. It is very effective on dried oil films. When cleaning from "black" to "white" and from "black" to grain it is a useful final treatment.

Directions for use

Cleaning of steam boilers

Fill the boiler with a 5-10% solution of Careclean Alkaline Extra in water. Depending on the degree of contamination allow this solution to circulate for 12 to 24 hours at a temperature of 80°C. After this boil out operation completely drain away the warm cleaning liquid and rinse the boiler intensively with cold water.

Tank recirculation method

Careclean Alkaline Extra is added to a mixing tank containing a water quantity of 1% of the capacity of the tank to be cleaned. The solution is heated by using the heating coils in the tanks. The

tanks are washed by using a cargo pump after which the solution is recycled to the mixing tanks. Usually one solution can be used to wash 2-3 tanks. Careclean Alkaline Extra is circulated as a 1-3% solution at 80-90°C for a period of 2-6 hours. After circulation rinse thoroughly with water.

Direct injection method

Inject 1-2 litres of Careclean Alkaline Extra per 100 litres of wash water directly into the tank washing system. The recommended cleaning temperature is 80°C. When completed rinse thoroughly with water.

Closing remarks regarding rinsing

In many cases an after treatment with Careclean Rust solution is recommended for the removal of white lime deposits originating from sea water and/or residues out of the cargo. Inject 0.5 litre Careclean Rust per 100 litres of wash water directly into the tank washing system for approx. 20 minutes. The recommended temperature is 75-85 °C. Finally wash the tanks thoroughly with cold fresh water.

For detailed instruction on tankcleaning refer to the Careclean Tank Cleaning Manual. A range of support equipment is also available.

Properties

Strong Alkaline liquid. suitable for use on epoxy coatings and most common metals except aluminium, tin, zinc, galvanised materials and zinc silicate coatings.

Specific gravity (20°C) : 1.34

Flash point : none

pH (1% solution) : 12.8

Contains approx. 30% Sodium Hydroxide.

For detailed information on safety and health, please refer to Material Safety Data Sheet and / or Product label.

The details of our products are given completely free of undertaking. Since their application lies outside our control we cannot accept any liability for the results.